

XQ-100301P50 / XQ-100302P50 / XQ-100303P50 / XQ-100304P50


| 型号 | Model Code | XQ-100301P50 | XQ-100302P50 | XQ-100303P50 | XQ-100304P50 |
|----|--------------|--------------|--------------|--------------|--------------|
| 功率 | Power | 6W | 6W | 6W | 6W |
| 开孔 | Cut out | Φ50mm | Φ50mm | Φ50mm | Φ50mm |
| 光源 | Light Source | CREE | CREE | CREE | CREE |
| 尺寸 | Size(LxWxH) | 60x60x75mm | 60x60x78mm | 60x60x75mm | 60x60x78mm |

| | | | | | |
|------|------------|-------------|-------------|-------------|-------------|
| 眩光值 | UGR | <19 | <19 | <19 | <19 |
| 显色指数 | CRI | ≥80/≥90 | ≥80/≥90 | ≥80/≥90 | ≥80/≥90 |
| 光束角 | Beam angle | 15°/24°/38° | 15°/24°/38° | 15°/24°/38° | 15°/24°/38° |


| | | | | | |
|------|-----------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| 色温 | CCT | 2700K/3000K/4000K/5000K | 2700K/3000K/4000K/5000K | 2700K/3000K/4000K/5000K | 2700K/3000K/4000K/5000K |
| 光通量 | Lumens | 308 lm/338 lm/354 lm/376 lm | 308 lm/338 lm/354 lm/376 lm | 283 lm/312 lm/326 lm/346 lm | 283 lm/312 lm/326 lm/346 lm |
| 寿命 | Life time | 50000 h | 50000 h | 50000 h | 50000 h |
| 防护等级 | IP | IP20 / IP65 | IP20 / IP65 | IP20 / IP65 | IP20 / IP65 |

配光参数 Photometric

Beam Angle 15° 6W 3000K



Beam Angle 24° 6W 3000K



Beam Angle 38° 6W 3000K

